

Coatings for Tanks and Vessels:

Ceramic Polymer: Internal coating of a huge tank for brewery effluents in Laško, Slovenia with PROGUARD CN 200

Ceramic Polymer GmbH (Daimlerring 9 DE-32289 Roedinghausen

www.ceramic-polymer.de



>>>

The large wastewater tank of a well-established brewery in Laško showed heavy corrosion damages. Extreme rust perforation occurred in its upper third; the area with fluctuating water levels.

The sewage water contains an elevated oxygen level within this zone. Thus, this part of the tank is most susceptible to corrosion.



Before the restoration: Clearly visible perforation corrosion. The company ISDW sealed the holes and laminated the damaged spots with glass fiber.

Brewery effluents have high pH values and an extensive chemical aggressiveness due to organic substances such as yeast, starch or sugar compounds. Moreover, plenty of chemical detergents are fed into the sewage of breweries.

The wastewater tank in Laško was completely and extensively renovated. For instance, only assembling the scaffold takes approximately 2 weeks. The German company ISDW used for the new coating of the tank our product system PROGUARD CN 200.



Firstly, the area was sandblasted.

Technical Details

Project: Restoration of huge tank for brewery effluents

Height of the tank: 18 m

Diameter: 22 m

Coated area: 1000 m² wall area Coating product: PROGUARD CN 200

Application of the coating:

ISDW GmbH, DE-Mittenwalde/Germany

newsletter 09 2016



Pre-coating of welds and rivets with PROGUARD CN 200.



Application of the coating system PROGUARD CN 200 by airless spraying.



Extra, flexible sealing of rivets, welds and abutting edges.



Our partner for professional surface protection

ISDW GmbH

Am Kanal, Gebaeude 23
DE-15749 Mittenwalde/Germany
Phone: +49 (0) 3 37 64 / 2 45 85

Email: isdw-gmbh@t-online.de

Web: www.isdw-gmbh.de

Contact Ceramic Polymer GmbH:

David Garcia Simao (Director) +49-5223-96276-15 dgs@ceramic-polymer.de

Woldemar Haak (Sales Management) +49-5223-96276-13 | wha@ceramic-polymer.de

Our Product:

- Proguard CN 200



First section completed – the upper area is coated.

- excellent chemical resistance
- high abrasion resistance
- temperature stability up to 130 °C (266 °F) for wet storage substances
- · long-term corrosion protection for all kinds of effluents
- 1-layer-system
- short curing times
- solvent-free



Do you need resistant coatings to protect from chemicals and sewage water? We provide customized product solutions for your application case!